

DF-660

SURGICAL **SUCTION UNIT**

(Aspirator)





The aluminum bottle rack offers more space for collection bottles and enlarges the capacity. According to user's preference, reusable and disposable bottles are able to install. Autoclavable and reusable PC collection bottle is factory equipped.



The fan is designed to prevent heat and make pump works efficiency.

Lower center of gravity makes it moving stable and smoothly; caster with locking



A spacious storage platform for instrument.



The tube holder is to hold the suction tube, catheter or suction instrument.



Depositing box creates extra space for storage.



Foot switch is to operate the machine and dual-fuse safety design may shut off electricity when overloaded.

brake improving safety.

Standard Accessory	
Suction tube (S)180cm	1 pc
Suction catheter	1 pc
Foot switch	1 pc
Filter (L)	2 pcs

Specification

Vacuum range	> 650 mmHg
Max. flow rate	120 L/min
Capacity	3000 c.c. x 2pcs
Safety device	Floating control
N.W. / G.W.	24 kg / 28 kg
Machine size	L45xW40xH90 (cm)
Packing size	L52xW48xH94 (cm)

90-056 Oil-less Piston Vacuum Pump

DOCTOR'S FRIEND or con



Thermal protector, auto reset.

Pump specification

Voltage	120V / 240V
Current	3.5A / 1.7A
Capacitor	40uf / 13uf
R.P.M.	1720 / 1450 rpm
Output	375 W
Max. flow rate	120 L/min
Vacuum range	> 650 mmHg
Weight	8.3 kg





No.28, Ln. 13, Sec. 3, Zhongshan Rd., Tanzi Dist., Taichung City 42756, Taiwan TEL: +886-425347777 FAX: +886-425338669 Email: medical.df@msa.hinet.net

